



Concrete skip of cylindrical/conical shape, with straight outlet and hose coupling. Commands for opening and closing discharge valves and for the external vibrator are given by means of a radio control system with a range of 600m. The opening mechanism is operated via a hydraulic cylinder. The concrete skip is built in conformance with official labour safety regulations. Safety requirements, such as automatic closing of the valve in the event of malfunctions or range violations, are met.



Cap.	D	S	H1	H2	H	HB	Wt
500	1040	1040	1350	300	1650	2170	300
750	1400	1400	1350	250	1600	2300	370
1000	1400	1400	1350	400	1750	2450	400
1250	1600	1600	1350	350	1700	2500	430
1500	1600	1600	1350	450	1800	2600	515
1750	1600	1600	1350	600	1950	2750	550
2000	1800	1800	1500	500	2000	2900	710
2500	1800	1800	1500	700	2260	3100	740
3000	2000	2000	1500	600	2200	3150	850

A: 200 Ø Standard 150, Ø 300, Ø optional

*Lifting & Handling Solutions for the Construction Industry
Designed & Manufactured in the UK*

Conquip Industrial, Waterbrook Estate, Waterbrook Road, Alton, Hampshire, GU34 2UD. United Kingdom
Telephone; +44 (0) 845 201 5030 **Fax;** +44 (0) 845 201 5031 **E-Mail;** sales@conquipindustrial.co.uk